

I4FP-22W 22" WIDESCREEN HIGH BRIGHTNESS OPEN FRAME LCD PANEL

High Brightness



- Wide 22" industrial TFT LCD panel
- Universal open frame mounting for various applications
- OSD control keys to optimize the display
- Fits a wide range of mounting kits
- Suggested usage: Industrial process control, point of sales / Kiosk, security / surveillance, flight information display panel

Specifications			
Max Resolution	1680 x 1050	Material	1.2mm steel
Brightness	800 cd/m2	Color	Black
Color Support	16.7 Mil	Input Video Signal	Analog RGB
Contrast Ratio	900 : 1	Video Level	Analog: 0.7Vp-p
Response Time	3.6 ms	Sync Type	Separate H/V, Composite H/V
Pixel Pitch	0.282 x 0.282	Input Connector	D-Sub 15 pin VGA analog
Display Area	474 x 296 mm (HxV)	Power Input	Auto-sensing 100 to 240VAC, 50/60 Hz via AC adapter
Viewing Angle	80° / 80° / 80° / 80° (L/R/U/D)	Power Consumption	Max. 84 watt, Standby 5 Watt
OSD Control	Color, brightness, phase & clock, auto-tune & recall, contrast, H & V position	Temperature	Operation: 0° to 50°C Storage: -5° to 60°C Relative Humidity: 5~90%, non-condensing
MTBF	50,000 hrs	Shock & Vibration	10G acceleration (11ms duration) 5~500Hz 1G RMS random vibration
Dimension	571 x 55 x 377 mm (w x d x h)	Package Dimension	653 x 112 x 558 mm (w x d x h)
Weight	5kg	Package Weight	10kg

Available Options

BNC + S-video / DVI / HDMI
 TV tuner w/ remote controller
 Touchscreen (USB or Serial, e-Resistive or e-Capacitive)
 Quad display
 DC power (12VCD / 24VCD / 48VCD)
 Audio input
 Standard remote controller
 Anti-reflective film
 Optical bonding

I4FP-22W 22" Wide Screen High Brightness Open Frame LCD Panel

